



Product Sheet

Synthetic Gear Oil

Midas Synthetic Gear Oil is a versatile multi-grade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-140 viscosity. It is a premium extreme-pressure lubricant designed for use in conventional differentials, limited-slip differentials and manual transmissions. **Midas Synthetic Gear Oil** is a multi-use product that can be used in place of SAE 75W, SAE 80W-90, SAE 90 or SAE 80W-140 and SAE 85W-140 or SAE 140 oils.

Application / Directions

Follow vehicle manufacturer's recommendations for use of product.

Midas Synthetic Gear Oil is designed to be used in conjunction with **Midas** Differential/Driveline service and tools.

NOTE: Limited-slip differentials require the use of
Limited-Slip Concentrate .



Features / Benefits

- Superior lubrication and protection for bearings and gear teeth. Helps prevent wear, pitting and corrosion.
- Excellent fluidity in extreme temperature. Unlike other grades of gear oil, **Midas Synthetic Gear Oil** stays fluid in the hottest temperatures to below zero.
- Eliminates the need to inventory and use multiple gear oils for different weather conditions.
- **Midas Synthetic Gear Oil** provides proper lubrication in summer and winter.
- Helps reduce gear noise in all conditions due to it's multi-grade formula and increases driveline efficiency.
- Long drain life and reduce maintenance, plus shear-resistant formula maintains viscosity without the ill effects of ineffective viscosity improvers.
- Helps lower operating temperatures.

Part # 60001M

6 per case / 64oz